

BD/L : PLASTERING AND POINTING

Sr. No. & Item Code	Description of Items	Unit	in Rs Complete
1	Providing internal cement plaster 6 mm thick in single coat in without neeru finish to concrete surface in all positions including scaffolding, curing complete.		
	a) cement mortar 1:3 (Cement 0.07 bags per Sqm.)	Sqm.	
	b) cement mortar 1:4 (Cement 0.045 bags per Sqm.)	Sqm.	
2	Providing internal cement plaster 12 mm thick in a single coat in without neeru finish to concrete or brick surfaces in all positions including scaffolding, and curing complete.		
	a) cement mortar 1:3 (Cement 0.14 bags per Sqm.)	Sqm.	
	b) cement mortar 1:4 (Cement 0.11 bags per Sqm.)	Sqm.	
	c) cement mortar 1:5 (Cement 0.09 bags per Sqm.)	Sqm.	
3	Providing internal Cement Plaster 20 mm thick in a single coat in cement mortar 1:4 without neeru finish to stone masonry surfaces in all positions including scaffolding and curing complete.	Sqm.	
	(Cement 0.17 bags per Sqm.)		
4	Providing internal Cement Plaster in all positions including scaffolding and curing complete.		
	a) 20 mm thick in a single coat in cement mortar 1:5 without neeru finish to concrete or brick surfaces (Cement 0.145 bags per Sqm.)	Sqm.	
	b) 20 mm thick in two coats in cement mortar 1:4 without neeru finish to concrete or brick surfaces (Cement 0.176 bags per Sqm.)	Sqm.	
5	Providing internal Cement Plaster 25 mm thick in two coats in cement mortar 1:4 without neeru	Sqm.	

P-368 finish to concrete, brick or stone surfaces in all positions including scaffolding and curing complete. (Cement 0.176 bags per Sqm.)

Item Code	Description of Items	Unit	Complete
6	Providing sand face plaster externally using approved screened sand in all positions including base coat of 15 mm thick in cement mortar 1:4 using water proofing compound at the rate of 1 Kilogramme per cement bag and curing the same for not less than two days and keeping the surface of base coat rough to receive the sand faced treatment not to exceed 8 mm thickness in cement mortar 1:4, finishing the surface by taking out grains and curing for 14 days and scaffolding etc. complete. (Cement 0.25 bags per Sqm.)	Sqm.	
7	Providing rough cast cement plaster externally in two coats to concrete/ brick/ stone masonry in all positions with base coat of 12 to 15 mm thick in cement mortar 1:4 and rough cast treatment 12 mm thick proportion 1:1½:3 including scaffolding and fourteen days curing complete. (Cement 0.25 bags per Sqm.)	Sqm.	
8	Providing neeru finish to plastered surfaces in all positions including scaffolding and curing complete.	Sqm.	
9	Providing stone-crete facing of approved colour and dressing with base coat of 12 to 15 mm thick in cement mortar 1:3 using water proofing compound at the rate of 1 Kilogramme per bag to brick/ stone/ concrete surfaces in all positions including final coat for stone-crete facing of required thickness but not less than 12 mm thick in proportion of 1:3 using gray cement and colour pigment including scaffolding and fourteen days curing, complete. (Cement 0.338 bags per Sqm.)	Sqm.	
10	Providing flush grooved pointing to with cement mortar 1:3 including scaffolding and curing complete.		
	a) brick masonry (Cement 0.03 bags per Sqm.)	Sqm.	
	b) stone masonry	Sqm.	

(Cement 0.025 bags per Sqm.)

Sr. No. & Item Code	Description of Items	Unit	in Rs. Complete
11	Providing Tuck pointing to stone masonry/brick work with cement mortar 1:3 including scaffolding and curing complete. (Cement 0.05 bags per Sqm.)	Sqm.	
12	Providing Weathered pointing to stone masonry/brick work with cement mortar 1:3 including scaffolding and curing complete. (Cement 0.04 bags per Sqm.)	Sqm.	
13	Providing Vee pointing to stone masonry/brick work with cement mortar 1:3 including scaffolding and curing complete. (Cement 0.03 bags per Sqm.)	Sqm.	
14	Removing the existing cement plaster of any thickness without causing dust nuisance and stacking the debris upto a distance of 50 metres or spreading in the compound and cleaning the site etc. complete. Spec : (As directed by Engineer in Charge) Note : Following items to be executed after prior approval of Superintending Engineer	Sqm.	
15	Providing 6 mm thick P.O.P. finish in single Coat to complete or brick surfaces in all positions including scaffolding etc. complete. Spec : (As directed by Engineer in Charge)	Sqm.	
16	Providing 12 mm thick P.O.P. finish in single coat to complete or brick surfaces in all positions including scaffolding etc. complete. Spec : (As directed by Engineer in Charge)	Sqm.	
